

# VBD-V

-  LIGHT WEIGHT
-  LOW ENERGY
-  SKD
-  NO NOISE
-  HD
-  EASY SERVICE
-  EASY METAL
-  RUGGED
-  IP65

		1.2 mm	1.6 mm
		RGB LED	RGB LED
		640,000 m <sup>2</sup>	360,000 m <sup>2</sup>
		200 × 150	200 × 150
		400 × 450 × 49	400 × 450 × 49
		2 × 3	2 × 3
		160 × 120	120 × 90
		320 × 360	240 × 270
		6.19 kg/	6.08 kg/
	14 - 16 bit	14 - 16 bit	14 - 16 bit
	281 trillion	281 trillion	281 trillion
	20000 : 1	20000 : 1	20000 : 1
	440	440 w/ m <sup>2</sup>	440 w/ m <sup>2</sup>
	-10 - 40	-10 - 40 / 10% - 90%	-10 - 40 / 10% - 90%
	-20 - 60	-20 - 60 / 10% - 90%	-20 - 60 / 10% - 90%
	600-800*nits	800-1000*nits	800-1000*nits
		3,840 Hz	3,840 Hz
		170°	170°
		170°	170°
		100,000 Hrs	100,000 Hrs
		IP 30	IP 30
		CE*, EMC* ,ClassA*,	CE*, EMC* ,ClassA*,

